

# PROCESS FILTER MACRO®PF

WTC-MACRO manufactures, supplies & installs process filters MACRO®PF.

#### **FEATURES**

- High capacity
- Standard units including flow and pressure control
- Corrosion resistant materials in polypropylene, acid proof steel (AISI 316L) or on request other materials
- Effective water treatment & guaranteed performance
- Special design for recirculation systems
- Easy handling to change filter material







### **APPLICATIONS**

- Active carbon filtration
- Biological filtration
- □ Oil/degrease filtration
- Recycling of liquids
- □ Recovery of rinse water & process liquids
- ☐ Pre-filtration before ion exchangers or membrane units
- Metal removal including ion exchange
- □ Complex ion removal
- □ Removal of detergents and other organic materials
- Bacteria removal



## Clean water

Sustainable environment



## PROCESS FILTER MACRO®PF

### Capacity from 15 - 20 m3/h

Туре	PF SS-20-0	PF PP-15-0
MATERIAL OF TANK	acid-proof steel	polypropylene
MATERIAL OF FRAME	PP and AISI 316	PP and AISI 316
FLOW (M3/H)	20	15
PRESSURE LOSS NEW BAG (BAR)	0,5	0,5
PRESSURE LOSS (BAR)	1,5	1,5
PRESSURE WORK (BAR)	2,5	2,5
TEMPERATURE MEDIA (°C)	90	90
TEMPERATURE AMBIENT (°C)	5-40	5-40
CONNEC. OUT/IN	D50 (nw 40)	D50 (nw 40)
INSULATION	IP55	IP55
MOTOR POWER (KW)	1,5	0,75
DIMENSIONS LXWXH (MM)	500 x 620 x 1100	500 x 620 x 1100
wеібнт (к <b>б</b> )	75	65
FILTER BAG MATR	upon request	upon request

<sup>\*</sup>The data in the table is indicative. The exact dimnesions are determined during the customizing of design for each system to fit the customer demand and individual site conditions.

